

Network Video Recorder

PRODUCT INFORMATION

ADVANTAGES

- Support Ultra 265/H.265/H.264 video formats
- 8/16/32 channel input
- Plug & Play with 8/16 independent PoE network interfaces(MCT-NVR-P08, MCT-NVR-P16)
- Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols
- VGA and HDMI independent output
- Up to 16 Megapixels resolution recording
- Support N+1 Hot spare
- ANR technology to enhance the storage reliability when the network is disconnected

MODEL	MCT-NVR-P08	MCT-NVR-P16	MCT-NVR-B32
			
Incoming Bandwidth	320Mbps	320Mbps	320Mbps
Outgoing Bandwidth	160Mbps	160Mbps	160Mbps
Remote Users	128	128	128
IP Video Input	8-ch	16-ch	32-ch
RCA Audio Input	1-ch	1-ch	1-ch
Hard Disk	2 STAT	4 STAT	8 STAT
Hard Disk Capacity	Up to 16TB for each HDD	Up to 16TB for each HDD	Up to 16TB for each HDD
PoE Interface	8 RJ45 10M/100M self-adaptive Ethernet Interface	16 RJ45 10M/100M self-adaptive Ethernet Interface	N/A
PoE Max Power	Max 30W for single port, Max 130W in total	Max 30W for single port, Max 150W in total	N/A
PoE Supported Standard	IEEE 802.3at, IEEE 802.3af	IEEE 802.3at, IEEE 802.3af	N/A
Working Temperature	-10 °C ~ 55 °C (14 °F ~ 131 °F)	-10 °C ~ 55 °C (14 °F ~ 131 °F)	-10 °C ~ 55 °C (14 °F ~ 131 °F)
Working Humidity	≤ 90% RH (non-condensing)	≤ 90% RH (non-condensing)	≤ 90% RH (non-condensing)
Power Consumption (without HDD)	≤ 20W	≤ 20W	≤ 25W
Weight (without HDD)	≤ 2.6Kg (5.73lb)	≤ 4Kg (8.82lb)	≤ 5.5Kg (12.13lb)
Dimensions	380mm × 322mm × 53mm (15.0"×12.7"×2.1")	400mm × 368mm × 74mm (15.7"×14.5"×2.9")	442mm × 426mm × 89mm (17.4"×16.8"×3.5")